

DUMP TRAILER – HEAVY DUTY



CAM
SUPERLINE

DUMP TRAILERS – HEAVY DUTY

STANDARD FEATURES

- Tubular Main Frame
- 10 Gauge Floor
- 12 Gauge Sides
- Diamond Plate Fenders
- EZ Lube Dexter Axles
- Slipper Spring Suspension
- Electric Brakes (2) Axles
- Remote Control with 15' Cord
- Slide Out Ladder Ramps (6')
- Split Barn Door Gate
- LED Lights – Rubber Mounted
- Lockable Battery Box
- Adjustable 2-5/16" Ball Coupler or Pintle
- Safety Chains
- Storage Tray
- 7K Bolt-on Drop Leg Jack
- Bolt-on D-Ring Tie Downs (4)
- Sealed Wiring Harness
- 7-Way RV Plug
- Charge Wire with Circuit Breaker
- Breakaway Switch
- Epoxy Primer
- Polyurethane Paint Finish
- Colors (standard): Black, Yellow, Red, Gray, Orange & Blue
- Two Year Warranty



Pallet Fork Carrier & Tie Down Rail




Gooseneck

SPECIFICATIONS

Model#	5CAM612LPHD	6CAM612LPHD	6CAM614LPHD	7CAM614LPHD	6CAM616LPHD	7CAM616LPHD
GVWR:	11,960 lbs.	13,800 lbs.	13,800 lbs.	16,100 lbs.	13,800 lbs.	16,100 lbs.
Empty Weight:	3,580 lbs.	3,740 lbs.	4,040 lbs.	4,080 lbs.	4,300 lbs.	4,340 lbs.
Payload:	8,380 lbs.	10,060 lbs.	9,760 lbs.	12,020 lbs.	9,500 lbs.	11,760 lbs.
Bed Size:	6' x 12'	6' x 12'	6' x 14'	6' x 14'	6' x 16'	6' x 16'
Volume Capacity:	4.6 Cubic Yards	4.6 Cubic Yards	5.2 Cubic Yards	5.2 Cubic Yards	6.1 Cubic Yards	6.1 Cubic Yards
Height of Deck:	27"	28"	30"	31"	30"	31"
Inside Bed Side Height:	20-1/2"	20-1/2"	20-1/2"	20-1/2"	20-1/2"	20-1/2"
Inside Width (102"):	72-1/2" (81-1/2")	72-1/2" (81-1/2")	72-1/2" (81-1/2")	72-1/2" (81-1/2")	72-1/2" (81-1/2")	72-1/2" (81-1/2")
2"x4" Full Height						
Stake Pockets:	11	11	11	11	11	11
Radial Tire Size:	225/75R15LRD	235/80R16LRE	235/80R16LRE	235/85R16LRG	235/80R16LRE	235/85R16LRG
Cylinders:	Two Telescopic	Two Telescopic	Two Telescopic	Two Telescopic	Two Telescopic	Two Telescopic

OPTIONS AVAILABLE

- 102" Width
- 15K Bolt-on Drop Leg Jack
- Pallet Fork Carrier (14' & 16' Only)
- Combination Spreader/Split Barn Door Gate
- Hydraulic Surge Brakes (Free Backing)
- Spare Tire and Wheel
- Spare Tire Mount
- 24" Expanded Metal Side Ext. (Removable)
- 44" Solid Sides with Barn Door Gate (Fixed)
- 4" Drop Axles
- Undercoating
- Mesh Tarp Roller Kit
- Gooseneck with Adjustable Coupler and 15K Jack
- Mud Flaps
- Tie Down Rail
- Wireless Remote
- Torflex Axles
- Aluminum Wheels
- 12-Volt Deep Cycle Battery
- 110-Volt Automatic Battery Charger
- 25K Ball Coupler
- Custom Colors



Authorized Dealer

CAM
SUPERLINE

www.camsuperline.com

CAM Superline, Inc.

4763 Zane Miller Drive • Waynesboro, PA 17268
(800) 378-7623 • Fax (800) 279-7578